John Quaif Qualified RPII/PIPA and games.

INSPECTION REPORT



Paul Quaif Qualified RPII/PIPA Tester for inflatables and games.

Unit 28, Forest Business Park, Argall Avenue, London, E10 7FB

Email: paulqualf58@gmail.com Website: www.pjentertainments.co.uk

Company Name FUNDA	Y EN	PATA INMENT	Address		collingers	
Telephone No O87	00_	113993		WES	TEND RD	
Email OFFIC	E (Q)	FUNDAY LTD	·com	TIP	MEE COS O AH	
Serial No:	2084	7 -	Date of	Inspection	: 29-05-24	
Name of Inspector:	PAUL QUAIF		Expiry Date of Inspection			
	SAMO			W x H) (m		
				facturer:	SAYS INFLAT	ANG
11101110	CHRISTMAS NR29 4RE		Date of Manufacture			
riace of mapeedion	0100	7100			2017	
Structure	_	Anch	norage		Blower	
Seams and webbing		Condition of ancho	r points	V	, Suitability	-
Bed panels and steps firm		Type of anchor poir	nt Welly	- CINCY	Inlet and outlet mesh	-
Walls and towers firm	Number of anchors				Cable and plug	-
Grounding 65 KG		Anchor accessories		V	Impeller	
Sharp angles	V	Structura	l Materials		Return flap	
Pressure (water gauge) 42	y 2 Zips			1 /	PAT test	-
Entrapment	Ropes			NIA.	Blower type/electric	-
Stability	Windows/netting			'V	Motor cover/casing	1
Deflation / evacuation time	lation / evacuation time				Inhouse tested (PAT)	
Air loss		Slide platform heig			Blower size (Hp)	5
Check toys/obstacles	A	Height of walls (134	_		Blower tube length (m)	-2
Markings (AGE)	V	Height of walls (m)			Number of blowers (this unit)	
Identification //	Run Out (m)		\triangle		Petrol blowers only (4hp)	<u>+</u>
Art work (no significant peeling)			/ladder [\]		Play Area (L x W) (m)	
Fall off height (m)	1.4	Slide sheet			Number of users and user hei	ght
Open side fall off height (m)	.4		osed Structure		Maximum user height (m)	-2
Step and ramp size (m) R/5		Exits and markings			Maximum users at 1.0m	6
Internal wall height (m)	.3	Deflation of user a	rea		Maximum users at 1.2m	6
Stitching		Pressure or user area			Maximum users at 1.5m	0
Trough depth 10	140				Maximum users at 1.8	0
Fabric (fire retardant)			ON RESULTS		Customise max user height	
Fabric (strength)		PASS			Maximum users at customised	X
Thread (non-rotting)	4	FAIL			height	/

Notes/Risk Assessment: THE STEP IS A BIT SHORT OF THE STANDAN	Signature of tester	
IT HUST HAVE SAFETY MATS ARAIND ENTINE STET, VERY MINIMA	Paul Quaif	
RISK OF INJURY, MUST BE SURERVISOD AT ALL TIMES	John Quaif	

Comments:

This unit must always be used with 2-inch thick, high-density crash mats on all entrances and exits at a minimum of 1.2m from the unit. DO NOT operate in wind speeds in excess of 24mph/38kph.

This unit must always be supervised by a competent adult who is capable of exercising authority over the users.

I certify that the above equipment has been inspected to RPII standards as indicated and complies with the current health and safety notes on inflatable play, BSEN14960 has been adopted where appropriate on the above inspection report.

If the above equipment is an inflatable used for part of a game, I deem this item fit for purpose.

All anchor points must be used to secure the unit to the ground at all times.